

BEST AVAILABLE COPY



(19)

(11) Publication number:

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 07115270

(51) Intl. Cl.: G01N 27/416 G01N 27/28 G01N 2

(22) Application date: 18.04.95

(30) Priority:

(43) Date of application publication: 01.11.96

(84) Designated contracting states:

(71) Applicant: CASIO COMPUT CO LTD

(72) Inventor: TOYAMA TADAHISA

(74) Representative:



(54) BIOSENSOR

(57) Abstract:

PURPOSE: To provide a biosensor by which a measurement can be performed quickly and stably.

CONSTITUTION: A working electrode 12 is formed on the surface of a continuous porous substrate 11, a counter electrode 13 is formed on the rear, and the continuous porous substrate 11 is formed in such a way that a small-diameter porous substrate 11a having a pore diameter of about 0.2 μ m and a large-diameter porous substrate 11b having a pore diameter of about 100 μ m are bonded. A biosensor is constituted in such a way that an enzyme is immobilized inside the small-diameter porous substrate 11a and that no enzyme is immobilized inside the large-diameter porous substrate 11b. By this constitution, a liquid specimen creeps quickly into the large-diameter porous substrate 11b, and the liquid specimen creeps uniformly from the circumference of the small-diameter porous substrate 11a, and a substrate concentration can be measured quickly and stably.

COPYRIGHT: (C)1996,JPO



BEST AVAILABLE COPY

